

HST-T-IIIIX

- Multi zone alarm-6 zone
- DSP technology
- Simplify PCB. Better for installation and after service

Technical specification

- Electric current: AC215V~230V 50/60Hz
- Power: 35W
- Work environment: -10°C~+45°C
- Gross Weight: 71kg
- Outer frame: 2220mm (h) x 820mm (w) X 630mm (d)
- Inner frame: 2000mm (h) X 700mm (w) X 560mm (d)

Characteristic:

- 6 Pinpoint zones to precisely identify multiple target locations from head to toe.
- Synchronous alarm for different zones.
- Advanced broadband detection technology: can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from Level 0 to 99
High: Can detect a coin
Low: Detect big metal articles such as: knife, gun, and copper, aluminums, zinc (more than 150g), ignoring metal in belt button, shoes.
- Shock proof to avoid false alarm
- Sound and light alarm
- Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- Tamper-Proof: operate program is protected by password.
- Adjustable operating frequencies eliminate the potential effects from X-ray units, radios and other electrical interference sources.
- Mix distance between two Walk-thru: 0.4 meters at low sensitivity, 1.0 meters at high sensitivity
- Harmless to pregnant woman and heart pacemaker



Standards:

- In accordance with: NILECJ-0601
- CE Certificate; ISO 9001:2000 Certificate
- National standard

Function:

Walkthrough Metal Detector can easily detect weapons, such as knife and gun, and any metal articles which are hidden in human body.